

B13  
cancel.

rotary member, and the output shaft is supported relative to the through-hole of the vibration member at a position substantially corresponding to a node of a vibration generated in the vibration member within the through-hole of the vibration members.--.

✓ IN THE CLAIMS:

✓ Please cancel Claim 6 without prejudice to or disclaimer of the subject matter recited therein.

Please amend Claims 1 and 9, as follows. A marked-up copy of Claims 1 and 9, showing the changes thereto, is attached. Note that all the claims currently pending in the application, including those presently amended, have been reproduced below for the Examiner's convenience.

B13

1. (Twice Amended) A vibration wave driving apparatus comprising:

a vibration member formed by an elastic member having an electro-mechanical energy conversion element fixed thereto, and having a through-hole extending through a central portion thereof;

a support member fixed to said vibration member;

a rotary member in press contact with said vibration member, and having a through-hole extending through a central portion thereof;

B13  
cont.

an output shaft extending through the through-hole of said vibration member and the through-hole of said rotary member, and rotatable with said rotary member;

a case packaging said vibration member and said rotary member therein, and fixing one end portion of said support member, thereby supporting said vibration member; and

a plurality of bearings provided in said case, said plurality of bearings rotatably supporting said output shaft,

wherein the output shaft supports said vibration member at a position substantially corresponding to a node of a vibration generated in said vibration member, within the through-hole of said vibration member.

2. (Amended) A vibration wave driving apparatus according to Claim 1, wherein at least a portion of the through-hole of said vibration member provides a bearing surface.

3. A vibration wave driving apparatus according to Claim 1, wherein the through-hole of said vibration member has a bearing supported by said output shaft.

4. A vibration wave driving apparatus according to Claim 3, wherein the bearing in the through-hole of said vibration member supported by said output shaft is a sliding bearing.